

WHAT IS CLAIMED IS:

5 ⁵⁴⁷ 1. A screen for allowing a light generated by a light source and modulated by a picture display device having pixels laid out to form a matrix to produce an image thereon to be projected by using a projection optical means on said screen as an enlarged picture, said screen comprising:

a Fresnel lens sheet placed on an emission side of said picture display device;

a first configuration element having:

10 lenticular lenses provided on an incidence side of a light passing through said Fresnel lens sheet; and

15 light absorbing layers each provided at a place in close proximity to the focal point of one of said lenticular lenses and are separated from each other by a predetermined distance for forming a light passing unit; and

a second configuration element having a light passing plate fixed on said emission side of said first configuration element;

20 wherein a pitch of said light passing units is made smaller than a pitch of pixels projected and enlarged on said screen from said image produced by said picture display device.

2. A screen according to claim 1 wherein an emission surface of said light passing plate is subjected to a reflection preventing process for preventing reflection of a visible light.

25 3. A screen according to claim 1 wherein, on an emission

side of said light passing plate, there is provided a reflection preventing film for preventing reflection of a visible light.

4. A screen according to claim 1 wherein a light scattering material is mixed inside said light passing plate.

5 5. A screen according to claim 1 wherein a light scattering layer is provided between said light passing plate and said first configuration element.

6. A screen according to claim 1 wherein:

10 Fresnel lenses of said Fresnel lens sheet are laid out at a pitch F_p ;

said light passing units are laid out in a horizontal direction of said screen at a pitch L_p ; and

a ratio L_p / F_p of said pitch L_p to said pitch F_p is set at a value in the range 1.588 to 1.649.

15 7. A screen for projecting an enlarged picture on said screen from a picture display apparatus including a light source, a picture display device implemented as a matrix of pixels each having a means for modulating the intensity of a light generated by said light source, and a projection optical means for
20 projecting said displayed picture appearing on said picture display device,

said screen comprising:

a first configuration element having a plurality of lenticular lenses provided on a light- emission side of said
25 picture display device and light absorbing layers provided on

a light- emission side of said Lenticular lenses, and

a light passing second configuration element provided on
said light- emission side of said first configuration element,

said lenticular lenses having a longitudinal direction
5 coinciding with a screen surface vertical direction and laid
out contiguously in a screen surface horizontal direction; and

said light absorbing layers sandwiched by boundaries of
any two adjacent openings each provided at a location in close
proximity to a focal point of one of said lenticular lenses
10 associated with said opening;

wherein:

said first and second configuration elements are bound or
stuck to each other;

a pitch of said openings is made smaller than a pitch of
pixels projected and enlarged on said screen from said displayed
picture output by said picture display device; and
15

a pitch of interference lines caused by both interference
sources is set at a value about equal to or smaller than said
pitch of pixels projected and enlarged on said screen from said
20 displayed picture output by said picture display device.

8. A screen according to claim 7 wherein an emission
surface of said second configuration element is subjected to
a reflection preventing process for preventing reflection of
a visible light.

25 9. A screen according to claim 7 wherein, on an emission

side of said second configuration element, there is provided a reflection preventing film for preventing reflection of a visible light.

5 10. A screen according to claim 7 wherein a light scattering material is mixed inside said second configuration element.

11. A screen according to claim 7 wherein a light scattering layer is provided between said second configuration element and said first configuration element.

10 12. A screen according to claim 7 wherein:
a third configuration element having Fresnel lenses is provided on a light- incidence side of said first configuration element;

15 said Fresnel lenses of said third configuration element are laid out at a lens pitch F_p ;

said openings of said first configuration element are laid out in a horizontal direction of said screen at a pitch L_p ;

a ratio L_p / F_p of said lens pitch L_p to said pitch F_p is set at a value in the range 1.588 to 1.649;

20 a pitch M_{pl} of moire lines caused by both interference sources is set at a value smaller than a pitch I_{ph} of pixels projected and enlarged on said screen in a screen horizontal direction from said displayed picture output by said picture display device; and

25 a pitch of interference lines caused by said both

04453-10050

interference sources_is set at a value about equal to or smaller than a pitch of pixels projected and enlarged on said screen from said displayed picture output by said picture display device.

5 13. A projection- type picture display apparatus comprising:

 a light source;

 a picture display device implemented as a matrix of pixels for modulating the intensity of a light generated by said light source; and

 a projection optical means for projecting a picture appearing on said picture display device,

 a Fresnel lens sheet placed on an emission side of said picture display device;

 a first configuration element having:

 lenticular lenses provided on an incidence side of a light passing through said Fresnel lens sheet; and

 light absorbing layers each provided at a place in close proximity to the focal point of one of said lenticular lenses and are separated from each other by a predetermined distance for forming a light passing unit;

 a second configuration element having a light passing plate fixed on said emission side of said first configuration element;

25 and

wherein: a pitch of said light passing units is made smaller than a pitch of pixels projected and enlarged on a screen by said picture display device.

5 14. A projection- type picture display apparatus according to claim 13 wherein, on an emission side of said light passing plate, there is provided a reflection preventing film for preventing reflection of a visible light.

10 15. A projection- type picture display apparatus according to claim 13 wherein a light scattering material is mixed inside said light passing plate.

16. A projection- type picture display apparatus according to claim 13 wherein a light scattering layer is provided between said light passing plate and said first configuration element.

15 17. A projection- type picture display apparatus according to claim 13 wherein:

Fresnel lenses of said Fresnel lens sheet are laid out at a pitch F_p ;

20 said light passing units are laid out in a horizontal direction of said screen at a pitch L_p ; and

a ratio L_p / F_p of said pitch L_p to said pitch F_p is set at a value in the range 1.588 to 1.649.

18. A projection- type picture display apparatus comprising:

25 a light source;

a picture display device implemented as a matrix of pixels each having a means for modulating the intensity of a light generated by said light source;

5 a projection optical means for projecting a displayed image appearing on said picture display device; and

a screen used by said projection optical means to project said displayed image as an enlarge picture and provided with:

10 a first configuration element having a plurality of lenticular lenses provided on a light- emission side of said picture display device and light absorbing layers provided on a light- emission side of said lenticular lenses, and

15 a light passing second configuration element provided on said light- emission side of said first configuration element,

said lenticular lenses having a longitudinal direction coinciding with a screen surface vertical direction and laid out contiguously in a screen surface horizontal direction;

20 said light absorbing layers sandwiched by boundaries of any two adjacent openings each provided at a location in close proximity to a focal point of one of said lenticular lenses associated with said opening; and

said first and second configuration elements are bound or stuck to each other,

wherein:

25 a pitch of said openings is made smaller than a pitch of

pixels projected and enlarged on said screen from said displayed image output by said picture display device; and

a pitch of interference lines caused by both interference sources_is set at a value about equal to or smaller than said pitch of pixels projected and enlarged on said screen from said displayed image output by said picture display device.

19. A projection- type picture display apparatus according to claim 18 wherein an emission surface of said second configuration element is subjected to a reflection preventing process for preventing reflection of a visible light.

20. A projection- type picture display apparatus according to claim 18 wherein a light scattering material is mixed inside said second configuration element.

21. A projection- type picture display apparatus according to claim 18 wherein a light scattering layer is provided between said second configuration element and said first configuration element.

22. A projection- type picture display apparatus according to claim 18 wherein:

a third configuration element having Fresnel lenses is provided on a light- incidence side of said first configuration element;

said Fresnel lenses of said third configuration element are laid out at a lens pitch F_p ;

said openings of said first configuration element are laid

out in a horizontal direction of said screen at a pitch L_p ;

a ratio L_p / F_p of said lens pitch L_p to said pitch F_p is set at a value in the range 1.588 to 1.649;

5 a pitch M_{p1} of moire lines caused by both interference sources is set at a value smaller than a pitch I_{ph} of pixels projected and enlarged on said screen in a screen horizontal direction from said displayed image output by said picture display device; and

10 a pitch of interference lines caused by said both interference sources is set at a value about equal to or smaller than a pitch of pixels projected and enlarged on said screen from said displayed picture output by said picture display device.

23. A screen comprising:

15 a Fresnel lens sheet;

a first configuration element having:

lenticular lenses provided on an incidence side of a light passing through said Fresnel lens sheet; and

20 light absorbing layers each provided at a place in close proximity to the focal point of one of said lenticular lenses and are separated from each other by a predetermined distance for forming a light passing unit; and

25 a second configuration element having a light passing plate fixed on said emission side of said first configuration element;

wherein a pitch of said light passing units is made smaller than a pitch of pixels projected and enlarged on said screen from said image produced by said picture display device.

24. A screen for projecting an enlarged picture on said screen from a picture display apparatus comprising:

a first configuration element having a plurality of lenticular lenses provided on a light- emission side of said picture display device and light absorbing layers provided on a light- emission side of said Lenticular lenses, and

a light passing second configuration element provided on said light- emission side of said first configuration element,

said lenticular lenses having a longitudinal direction coinciding with a screen surface vertical direction and laid out contiguously in a screen surface horizontal direction; and

said light absorbing layers sandwiched by boundaries of any two adjacent openings each provided at a location in close proximity to a focal point of one of said lenticular lenses associated with said opening;

wherein:

said first and second configuration elements are bound or stuck to each other;

a pitch of said openings is made smaller than a pitch of pixels projected and enlarged on said screen from said displayed picture output by said picture display device; and

a pitch of interference lines caused by both interference

sources is set at a value about equal to or smaller than said pitch of pixels projected and enlarged on said screen from said displayed picture output by said picture display device.

add
a5

add
B2

663007-3267460